

Weight Classes Sat. Afternoon

3.5MPH: 3,500lbs, 3,750lbs, 4,000lbs, 4,500lbs, 5,000lbs, 5,500lbs, 6,000lbs, 6,500lbs, 7,500lbs.

6MPH: 3,500lbs, 3,750lbs, 4,500lbs, 5,000lbs
6,500lbs, (8,500lbs, 9,500lbs
10,500lbs, 11,500lbs, **(6MPH ONLY)**)

KING OF THE HILL: 5,500, 7,500 (NO SPEED LIMIT!)

\$25 Per Hook, NO REFUNDS!

Registration Time: 9 a.m. to 12 p.m. at the registration booth. pull starts at 12 p.m.

Pre- Registration and info please call Ricky Larsen

All Brands of Tractors Welcome!(Must be 40 years old or older)

Contact Info: Ricky Larsen 320-733-0111, call or text.

Rules:

1. ALL SAFETY EQUIPMENT IS RECOMMENDED BUT NOT REQUIRED.
2. ALL PULLING HITCHES MUST BE 3" WIDE BY 3 3/4" LONG AND 3/4" THICK WITH 1" THICKNESS AROUND THE HOLE. **NO HAMMER STRAPS. PULLING HITCHES OR CLEVICES ONLY.**
3. ALL ENGINE FANS MUST BE FACTORY OR SHROUDED STEEL 1/16" OR THICKER. AFTER MARKET (ELECTRICAL INCLUDED) MUST APPEAR STOCK.
4. NO PART OF THE TRACTOR MAY INTERFERE WITH THE SLED DURING THE PULL. NO WEIGHT FRAME OR WEIGHTS MAY EXTEND MORE THAN 11 FEET FROM THE CENTER OF REAR AXLE TO FRONT POINT OF WEIGHTS. ALL WEIGHTS MUST BE SAFELY SECURED TO TRACTOR AND CANNOT BE ON 2-OR-3 POINT ARMS. HITCH MUST BE CLEAR FOR HOOK, ANY ITEMS THAT FALL FROM TRACTOR DURING PULL WILL RESULT IN DISQUALIFICATION.
5. ALL IGNITION ENGINES MUST HAVE A KILL SWITCH IN WORKING ORDER WITHIN EASY REACH OF DRIVER.
6. ALL EXHAUST MUST BE FACTORY OR DISCHARGED VERTICALLY UPWARD ABOVE THE HIGHEST POINT OF THE TRACTOR. UNLESS FACTORY EQUIPPED DIFFERENTLY. MUST HAVE STOCK MANIFOLD, CARBURETOR, AND HEAD. TURBOS WILL BE ALLOWED AT 8,500 AND ABOVE.
7. ALL CLASSES WILL USE STANDARD DRAWBAR RULES. MINIMUM DRAWBAR LENGTH OF 18" FROM THE CENTER OF REAR WHEEL TO POINT OF HOOK MEASURED HORIZONTALLY, DRAWBAR MUST BE STATIONARY IN ALL DIRECTIONS. MAXIMUM DRAWBAR HEIGHT OF 20" FROM HITCH POINT PARALLEL TO THE GROUND. PULL POINT MAY NOT BE MORE THAN 1 1/2" FROM BACK EDGE OF HITCHING DEVICE. NO BRACING DRAWBAR TO 3-POINT TOP LINK. MUST FURNISH OWN HITCH. DRAWBAR MUST BE EASILY ACCESSIBLE. **(NO WEIGHTS BLOCKING IT.)**
8. OPERATOR MUST REMAIN SEATED AND ALWAYS HAVE COMPLETE CONTROL OF THE TRACTOR. ALL TRACTORS MUST HAVE WORKING REAR BRAKES.
9. TRACTORS MAY BE DOWNSHIFTED DURING PULL PROVIDED FORWARD MOTION IS CONSTANT. USE OF TORQUE AMPLIFIERS AND POWER SHIFTS ARE ALLOWED.
10. ANY PULLER MAY HAVE ONE RE-PULL IF THE PULLER STOPS BEFORE THE FRONT OF THE SKID PASSES THE 100 FOOT MARK, AND REQUEST THE RE-PULL BEFORE THEY ARE UNHOOKED FROM THE SLED. NO FIRST PULLER RE-PULL OPTION.
11. ALL UNDERAGE DRIVERS MUST HAVE A PARENTAL PERMISSION SLIP SIGNED, NO EXCEPTIONS.
12. SPEED LIMIT WILL BE ENFORCED IN ALL CLASSES BY PLACING A CONE AT 100 FEET. ANY HORNS AFTER 100 FEET WILL RESULT IN DISQUALIFICATION OF THAT PULL. ANY HORNS BEFORE THE 100 FOOT MARK WILL NOT COUNT, REGARDLESS OF HOW MANY.
13. 2 HOOKS PER TRACTOR. 1% OVER ON WEIGHTS.

14. 3.5 MPH STOCK CLASS NO TOP CUT TIRE UNLESS PULLING IN POINT SERIES.

KING OF THE HILL: 5,500, 7,500 (NO SPEED LIMIT!)

Rules:

5,500 AND 7,500 OPEN CLASS.

1. ALL SAFETY EQUIPMENT REQUIRED.(WHEELY BARS, FENDERS, KILL SWITCH IN BACK OF TRACTORS).
2. FULL CUT AND TOP CUT TIRES ALLOWED.
3. ANY PULLER WILL HAVE THE OPTION FOR ONE RE-PULL IF THE PULL STOPS BEFORE THE FRONT OF THE SKID PASSES THE 100 FOOT MARK. THEY MUST REQUEST THE RE-PULL BEFORE THEY ARE UNHOOKED FROM THE SLED.
- 4.HITCHES MUST 3" WIDE BY 3 3/4" LONG AND 3/4" THICK WITH 1" THICKNESS AROUND THE HOLE. TWISTED CLEVICES OR PULLING HITCHES ONLY, NO EXCEPTIONS.
- 5.DRAWBAR RULES. MINIMUM DRAWBAR LENGTH OF 18" FROM THE CENTER OF REAR WHEEL TO POINT OF HOOK MEASURED HORIZONTALLY, DRAWBAR MUST BE STATIONARY IN ALL DIRECTIONS. MAXIMUM DRAWBAR HEIGHT OF 20" FROM HITCH POINT.

REGISTRATION TIME: 9 am to 12 pm. Pull starts at 12 pm.